

CLASSIFICATION

CONFIDENTIALCENTRAL INTELLIGENCE AGENCY
INFORMATION FROM
FOREIGN DOCUMENTS OR RADIO BROADCASTS

REPORT

CD NO.

50X1-HUM

COUNTRY USSR

SUBJECT Scientific - Engineering, Fuels, flammability

HOW PUBLISHED Monthly periodical

WHERE PUBLISHED Moscow

DATE PUBLISHED May 1950

LANGUAGE Russian

DATE OF INFORMATION 1950

DATE DIST. 18 Dec 1950

NO. OF PAGES 4

SUPPLEMENT TO
REPORT NO.

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE
OF THE UNITED STATES WITHIN THE MEANING OF ESPIONAGE ACT 50
U. S. C. 31 AND 32, AS AMENDED. ITS TRANSMISSION OR THE REVELATION
OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PRO-
HIBITED BY LAW. REPRODUCTION OF THIS FORM IS PROHIBITED.

THIS IS UNEVALUATED INFORMATION

SOURCE

Izvestiya Akademii Nauk SSSR, Otdeleniye Tekhnicheskikh Nauk, No 5,
1950, pp 682-694.

THE PHENOMENON OF FOAMING-OVER
OF HEAVY LIQUID FUELS
BURNING AT THE FREE SURFACE

G. N. Khudyakov,

Power Inst imeni Krzhizhanovskiy

Acad Sci USSR

Submitted 8 December 1949 by Acad A. V. Vinter

[Digest]

[The following is a brief description of the factors, under
laboratory conditions, that govern the foaming-over of heavy oil
burning in a container.]

Subject report discusses recent experiments on the phenomenon of boiling-over characteristic of heavy oil products when burning on the surface of water in a container. Similar experiments had already been conducted in 1943 on light petroleum fuels, with the conclusion that there is rapid establishment of constant velocity of combustion and insignificant heating of the oil in the depth of the liquid, with the result that a light fuel on top of water in a container burns quietly.

Later and recent tests with heavy oils show that they heat up continuously within the depths of the oil as the surface burns, that is, they do not acquire the stationary, and comparatively insignificant, vertical temperature gradient which is typical of light fuels. Heat penetrates the depth of the heavy oil and causes the formation of steam which, as in the geyser phenomenon, expands and ejects the oil and its burning surface layers.

- 1 -

CONFIDENTIAL

CLASSIFICATION

STATE	<input checked="" type="checkbox"/> NAVY	<input checked="" type="checkbox"/> NSRB	DISTRIBUTION							
ARMY	<input checked="" type="checkbox"/> AIR	<input checked="" type="checkbox"/> FBI								

CONFIDENTIAL

50X1-HUM

The significant factor is the water content of the heavy oil, which causes the foam and subsequent foaming-over of the oil. A relation is established between the volume of foam generated by one kilogram of heavy oil at 100° C and the moisture content w (0 to 8%). Volume is found to increase as much as 1,763 times. A dozen different heavy oils are tested and classified in one of two types: (a) explosive with instantaneous ejection of the total quantity of oil; (b) formation of stable foam and foaming-over.

[Table follows]

- 2 -

CONFIDENTIAL

Foaming of Fuel Burning in Laboratory Apparatus on Top of Water Surface

Petroleum Product	Liquid Fuel Temp Before Expt (in ° C)	Thickness of Liq Fuel Layer (mm)		Avg Temp of Upper Layer (in ° C)	Rate of Burning (mm/min)	Time in Which Foaming Over Occurs (min)	Type of Foaming Over	Remarks
		Before Expt	Before Foaming Over					
Benzene distilla- tion head	22	140	-	78	3.8	Does not occur		
Automobile gasoline	25	157	-	153	2.4	" " "		
Kerosene	25	146	-	208	1.5	" " "		
Solar oil	26	160	8.2	285	1.15	132	Boiling accompanied by spraying	
Transformer oil	25	140	30.8	410	1.05	104	Weakly ex- plosive	Multiple ejection with violent spraying of burn- ing oil
Crude petroleum (dry)	29	136	71.6	340	1.70	32	Explosive	50X1-HUM
Crude petroleum (5% moisture)	29	140	122.4	305	1.60	1	Foaming	
Fuel mazut (dry)	32	150	78	395	1.80	40	Explosive	Momentaneous ejection of total quantity of ma- zut

CONFIDENTIAL

- 3 -

CONFIDENTIAL

Petroleum Product	Liquid Fuel Temp Before Expt (in ° C)	Thickness of Liq Fuel Layer (mm)		Avg Temp of Upper Layer (in ° C)	Rate of Burning (mm/min)	Time in Which Foaming Over Occurs (min)	Type of Foaming Over	Remarks
		Before Expt	Before Foaming Over					
Fuel mazut (6% moisture)	32	160	136.2	320	1.70	14	Foaming	Until flame extinguished
Water-free heavy mazut	35	140	98	502	0.95	44	Explosive	Momentaneous ejection of total quan- tity of ma- zut
Heavy mazut (7% moisture)	35	144	130.4	419	0.91	15	Foaming	Until flame extinguished

CONFIDENTIAL

- END -
- 4 -

CONFIDENTIAL

50X1-HUM